GSM/GPRS modules

MultiOne GSM



GSM gate controller and communicator

- 1 optocoupler (voltage) input
- 1 relay output 230 VAC/24 VDC, NO/NC
- Output control in bistable or monostable mode (250 s)
- Power supply: 12–24 VAC or 10–30 VDC
- Sending and forwarding SMS to one specified phone number
- Output control from the pre-stored (250/500) phone numbers or control without caller ID

EasyCon GSM



Miniature GSM-based communicator and remote control (6x3 cm)

- 2 contact-controlled inputs
- 1 open collector output
- Control by SMS from an unlimited number of phones, by voice call from 1000 numbers
- Forwarding SMS and voice message to 8 phone numbers
- Programming by SMS, PC, Android and voice menu

ProCon GSM



GSM/GPRS-based communicator and remote control with standalone alarm panel function

- 5 contact-controlled inputs
- 1 NO/NC relay output, controllable by SMS from unlimited numbers and by voice call from 1000 numbers
- Sending SMS, voice message and Contact ID
- Programming by SMS, PC, Android and voice menu
- Expandable, own battery connection, event log

EasyLine GSM



Plug & Play miniature PSTN telephone line simulator (6x4 cm)

- 1 SMS contact input, 1 OC output
- Sending SMS to the user
- Signalling Contact ID and 4/2 protocol to the monitoring centre
- Programming by SMS or a telephone handset
- Output control from pre-stored numbers

ProLine GSM



Professional PSTN telephone line simulator

- Monitoring and supervision of the telephone line (PSTN)
- 2 contact-controlled inputs, 1 OC output, free to control from 1000 phone numbers
- Forwarding SMS and/or voice message to 8 phone numbers
- Signalling Contact ID and 4/2 protocol to the monitoring centre + Enigma, SIA IP
- Translating Contact ID into SMS (pairing 250 zones and 250 events)
- Expandable, own battery connection, event log

InterCom GSM



GSM module for intercom systems with up to 4 apartments

- 2 relay outputs, controllable by DTMF codes during the call
- Free gate opening function from 1000 phone numbers
- Mains power monitoring
- 16 000-event memory, continuous GSM signal strength check
- Night mode, own battery connection

ASC Global MAGYARORSZÁG


Signalling to the monitoring centre


Back-up telephone line


Taxi / lift / emergency call


GSM/GPRS/IP for alarm panels


Remote control: gate, barrier, garage


GSM line for telephone systems


Wireless intercom


Home automation (lighting, sauna, heating, irrigation)

ProRead programming software

You can use the ProRead program for the full programming of the GSM/GPRS modules. It needs no installation and starts instantly, recognises the connected GSM module and provides simple, clear programming. The GSM modules can be connected to your computer over USB or Bluetooth.

Sign up for our training!

Get to know our products and programming software at our free training. Besides the basics we also show special solutions. Sign up now: info@ascglobal.eu

Anti-Jammer System: the product can detect GSM jammers; **Bluetooth:** the product can also be connected over Bluetooth; **48/72:** the module can simulate a telephone line; **3-year warranty:** the product has a 3-year manufacturer's warranty; **Voice menu:** the module can also be programmed via a voice menu using the phone keys; **Plug&Play:** the module is easy to install and needs no separate programming; **ProRead:** professional programming software for programming the product from a computer over USB or Bluetooth; **AndroRead:** Android programming application for the wireless programming of our GSM products over Bluetooth; **Dual Memory:** the settings are stored in two places in the module.

	EasyLine GSM	ProLine GSM	MultiOne GSM	EasyCon GSM	ProCon GSM	InterCom GSM
Inputs (+expander)	1	2	1	2	4 (+1)	4
Outputs (+expander)	1	1(+3)	1	1	1 (+3)	2
User phone numbers for signalling	1	8	1	8	8	4 x 2
Monitoring centre phone numbers	✗	2	✗	2	2	✗
Caller ID	✓	✓	✓	✓	✓	✓
User phone numbers for output control	SIM	∞/1000	SIM	∞/1000		
Telephone line simulation	✓	✓	✗	✗	✗	✗
Transmission channel	GSM/SMS	PSTN/GSM/SMS/GPRS	GSM/SMS	GSM/SMS	GSM/SMS/GPRS	GSM/SMS/GPRS
Event list	✗	16000	✗	16 000		
Expandability	✗	✓	✗	✗	✓	✗
Battery connection	✗	✓	✗	✗	✓	✓
Programming mode	SMS	SMS/PC (USB/Bluetooth)	SMS	SMS/PC (USB/Bluetooth)		
Current draw	80mA/1000mA	80mA/1000mA	12V@25mA/700mA 24V@15mA/350mA	25mA /700mA	30mA /700mA	40mA /700mA

USABLE ACCESSORIES

PROGRAMMERS



EXPANSION BOARDS



ANTENNAS



OTHER ACCESSORIES



ASC Global
MAGYARORSZÁG

www.ascglobal.eu • info@ascglobal.eu • (+44) 20 3807 1345